



PROJECT

COMMENTS



IN STOCK



ENERGY CHART

SIZE	TOTAL DIAMETER inches	DELIVERED LUMENS	WATTAGE	EFFICACY lm/w
4	4.3	810	9	90

ORDERING LOGIC

EX: G4P-FS3

FAMILY CCT

G4P FS3

FS3 Field Selectable
3000K / 4000K / 5000K

G4P GIMBAL 4" PANEL LED

The G4P series is a glare-free adjustable panel light intended for new construction and retrofit applications. G4P is equipped with strong spring-loaded retention clips for recessing into ceilings up to 1" thick without the need for a J-box or recessed housing. G4P is IC rated, IP44 rated, and suitable for damp locations.

- Residential
- Commercial
- Hospitality

PHYSICAL

Material	Aluminum
Mounting	Recessed
Lens	PMMA
Finish	White

PERFORMANCE

Warranty	5 years
Certifications	Damp Location, IC Rated, ETL, CE, Energy Star, FCC, ROHS Compliant
IP Rating	IP44
Rated Life	L70 50,000 hours
Operating Temperature	-20°C to 40°C (-4°F to 104°F)
CCT	Field Selectable 3CCT: 3000K/4000K/5000K
CRI	80+
Adjustability	25° Tilt
Beam Angle	180°

ELECTRICAL

Wattage	9W
Voltage	120V
Power Factor	>0.95
Dimmable	100% - 5% Triac Dimming

