

PROJECT

COMMENTS

DATE

RoHS
Compliant

IN STOCK



CLEAR



MIRROR



WHITE



ELR EDGE-LIT EXIT RECESSED LED

The ELR Series offers a single or double, red or green LED face options complete with a test switch and recharge indicator. The ELR comes with bar hangers so it can easily be installed in drywall or drop ceilings.

- Residential
- Commercial
- Hospitality

PHYSICAL

Material	Aluminum Housing with High Grade Acrylic Panel
Mounting	Universal Recessed J-Box Mounting Pattern
Panel Finish	Clear, Mirror or White
Face Count	Universal, Single or Double
Letter Color	Green or Red

PERFORMANCE

Warranty	5 years
Certifications	UL, cULus, RoHS Compliant
Operating Temperature	0°C to 40°C (32°F to 104°F)

ELECTRICAL

Voltage	120V-277VAC
Wattage	3W
Battery	4.8V Nickel Cadmium 90-Minutes Emergency Operation

ORDERING LOGIC – UNIVERSAL FACE VERSION

EX: ELR-U-G-AC

FAMILY	FACE COUNT	LETTER COLOR	OPERATION
ELR	U		
	U Universal SINGLE CLEAR / DOUBLE MIRROR	G Green	AC AC Only
		R Red	EM Emergency (Nickel-Cadmium Battery)

ORDERING LOGIC – SINGLE OR DOUBLE VERSION

EX: ELR-CL-S-G-AC

FAMILY	PANEL FINISH	FACE COUNT	LETTER COLOR	OPERATION
ELR				
	CL Clear	S Single	G Green	AC AC Only
	MR Mirror	D Double	R Red	EM Emergency (Nickel-Cadmium Battery)
	WH White			

DIMENSIONS

