

PROJECT

DATE

COMMENTS



#### ENERGY CHART

SIZE	HEIGHT inches	WIDTH inches	WATTAGE
9	1.4	4.1	3
12	1.4	4.1	6
18	1.4	4.1	9
24	1.4	4.1	12

#### ORDERING LOGIC

FAMILY	SIZE	CCT	CRI
<b>UC</b>			<b>90</b>
	<b>9</b> 9"	<b>27</b> 2700K	<b>90</b> 90+
	<b>12</b> 12"	<b>30</b> 3000K	
	<b>18</b> 18"	<b>40</b> 4000K	
	<b>24</b> 24"		

## UC UNDER CABINET LED

The UC Under Cabinet LED Series is suitable for under cabinet mounting in dry locations. Capable of being converted to a fixed hard wire unit.

- Kitchen
- Bar
- Shelving

#### PHYSICAL

Material	Low Profile Polycarbonate Cover
Mounting	Surface
Lens	Opal Glass Diffuser
Source	LED

#### PERFORMANCE

Warranty	5 years
Certifications	ETL, CE
Operating Temperature	-30°C ~ 40°C (-22°F to +104°F)
CCT	2700K, 3000K, 4000K
CRI	90+

#### ELECTRICAL

Wattage	3W, 6W, 9W, 12W
Voltage	120V

EX: UC-9-27-90