

PROJECT COMMENTS 

ENERGY CHART

SIZE	HEIGHT inches	WIDTH inches	LUMENS	WATTAGE	EFFICACY lm/w
9	0.6	9.0	1530	18	85

ORDERING LOGIC

FAMILY	SIZE	CCT
SPR-MS	9	FS
	9" FS	Field Selectable 3000K / 4000K / 5000K

EX: SPR-MS-9-FS

SPR-MS SLIM PANEL ROUND LED WITH MOTION SENSOR

The SPR-MS Series offers a low-profile, high output surface mount LED luminaire with an integral PIR motion sensor that meets Energy Star's efficiency standards. SPR-MS is suitable for installation within a clothes closet storage space per the requirements in UL1598:2018 Ed. 4 Section 13.6 and NEC 410.16.

- Residential
- Commercial
- Hospitality

PHYSICAL

Mounting	Surface
Finish	White

PERFORMANCE

Warranty	5 years
Certifications	ETL, Energy Star, FCC, Closet Rated (UL1598:2018 Ed.4 Section 13.6 / NEC 410.16)
IP Rating	IP20
Rated Life	L70 50,000 hours
Operating Temperature	-20°C to 40°C (-4°F to +104°F)
CCT	Field Selectable: 3000K/4000K/5000K
CRI	80+
Beam Angle	120°

ELECTRICAL

Wattage	18W
Voltage	120V
Power Factor	>0.90
Dimmable	No

DIMENSIONS

Size 9

