

PROJECT

DATE

COMMENTS






PHYSICAL	
Material	Metal Back Plate
Mounting	Surface
Lens	PMMA
Finish	Brushed Nickel
Source	LED

PERFORMANCE	
Warranty	5 years
Certification	Damp Location, ETL, Energy Star
Rated Life	L70 50,000 hours
CCT	3000K, Field Selectable 5CCT: 2700K/3000K/3500K/4000K/5000K
CRI	80+ or 90+

ELECTRICAL	
Wattage	15W, 20W, 25W
Voltage	120V
Power Factor	>0.90
Dimmable	Yes

ORDERING LOGIC

EX: BELT-12-FS5-90

FAMILY	DIAMETER	CCT	CRI
BELT		FS5	90
	12 12"	FS5 Field Selectable 2700K / 3000K / 3500K / 4000K / 5000K	90 90+
	14 14"		
	16 16"		



ENERGY CHART			
DIAMETER inches	DELIVERED LUMENS	WATTAGE	EFFICACY lm/w
12	1200	15	80
14	1600	20	80
16	2000	25	80

RECOMMENDED DIMMERS		
LEVITON MODELS		
• 6674	• IPL06	• TBL03
LUTRON MODELS		
• CT-600P	• DLC-03P	• MACL-153MR-WH
• CTCL-153P	• AYCL-153P	• TG-600RP
• 6333-P	• S-600P	• SCL-153P
• DVCL-153P	• LGCL-153P	