

TERRAIN

SITE LIGHTING

PROJECT

DATE

COMMENTS



IN STOCK



ENERGY CHART

FAMILY	DELIVERED LUMENS	WATTAGE	EFFICACY lm/w
BR10	2290	26	115

BR10 BOLLARD LED

The BR10 Series offers a durable, corrosion resistant, die-cast aluminum base with a polycarbonate diffuser and a 360° beam angle.

- Residential
- Commercial
- Hospitality

PHYSICAL

Material	Aluminum
Mounting	Ground Cage
Lens	Polycarbonate Diffuser
Finish	Bronze
CCT	3000K, 4000K, 5000K, 6000K, Field Selectable 3CCT: 3000K/4000K/5000K
CRI	80+
Beam Angle	360°

PERFORMANCE

Warranty	5 years
Certifications	CUL, DLC
IP Rating	IP65
Rated Life	50,000 Hours
Operating Temperature	-40°C to 40°C (-40°F to 104°F)

ELECTRICAL

Wattage	26W
Voltage	120-277V
Dimmable	1-10V
Power Factor	≥0.9
THD	≤20%

ORDERING LOGIC

EX: BR10-30

FAMILY	CCT
BR10	
	30 3000K
	40 4000K
	50 5000K
	60 6000K
	FS Field Selectable 3000K / 4000K / 5000K



DIMENSIONS

