

PROJECT _____ DATE _____

COMMENTS _____



ELR EDGE-LIT EXIT RECESSED LED

The ELR Series offers a single or double, red or green LED face options complete with a test switch and recharge indicator. The ELR comes with bar hangers so it can easily be installed in drywall or drop ceilings.

- Residential
- Commercial
- Hospitality

PHYSICAL

Material	Aluminum Housing with High Grade Acrylic Panel
Mounting	Universal Recessed J-Box Mounting Pattern
Panel Finish	Clear, Mirror, White or Universal
Face Count	Single, Double or Universal
Letter Color	Green, Red or Universal

PERFORMANCE

Warranty	5 years
Certifications	UL, CUL, ROHS Compliant
Operating Temperature	0°C to 40°C (32°F to 104°F)

ELECTRICAL

Voltage	120V-277VAC
Wattage	3W
Battery	4.8V Nickel Cadmium 90-Minutes Emergency Operation

ORDERING LOGIC

EX: ELR-CL-S-G-AC

FAMILY	PANEL FINISH	FACE COUNT	LETTER COLOR	OPERATION
ELR				
	CL Clear	S Single	G Green	AC AC Only
	MR Mirror	D Double	R Red	EM Emergency (Nickel-cadmium battery)
	WH White	UNV Universal SINGLE / DOUBLE	UNV Universal GREEN / RED	
	UNV Universal CLEAR / MIRROR / WHITE			

DIMENSIONS

