

PROJECT	DATE
COMMENTS	









IN STOCK



CLEAR

















ELR EDGE-LIT EXIT RECESSED LED

The ELR Series offers a single or double, red or green LED face options complete with a test switch and recharge indicator. The ELR comes with bar hangers so it can easily be installed in drywall or drop ceilings.

- · Residential
- · Commercial
- Hospitality

PHYSICAL

Material	Aluminum Housing with High Grade Acrylic Panel
Mounting	Universal Recessed J-Box Mounting Pattern
Panel Finish	Clear, Mirror or White
Face Count	Universal, Single or Double
Letter Color	Green or Red

PERFORMANCE

Warranty	5 years
Certifications	UL, cULus, RoHS Compliant
Operating Temperature	0°C to 40°C (32°F to 104°F)

ELECTRICAL

Voltage	120V-277VAC
Wattage	3W
Battery	4.8V Nickel Cadmium 90-Minutes Emergency Operation

ORDERING LOGIC - UNIVERSAL FACE VERSION

EX: ELR-U-G-AC

FAMILY		FACE COUNT	LETTE	ER COLOR		OPERATION
ELR	R U					
	U	Universal SINGLE CLEAR / DOUBLE MIRROR	G	Green	AC	AC Only
			R	Red	EM	Emergency (Nickel-Cadmium Battery)

ORDERING LOGIC - SINGLE OR DOUBLE VERSION

EX: ELR-CL-S-G-AC

FAMILY	PANEL FINISH	FACE COUNT	LETTER COLOR	OPERATION	
ELR					
	CL Clear	S Single	G Green	AC AC Only	
	MR Mirror	D Double	R Red	EM Emergency (Nickel-Cadmium Battery)	
	WH White				



DIMENSIONS

