

PROJECT  DATE

COMMENTS



DOE RoHS Compliant

**DISCONTINUED**



**ENERGY CHART**

DEPTH inches	HEIGHT inches	WIDTH inches	DELIVERED LUMENS	WATTAGE	EFFICACY lm/w
4.2	5.2	12.3	400 total (200 per head)	2.4	167

**EMWL EMERGENCY WET LOCATION LED**

The EMWL is a 120V/277VAC dual voltage Wet Location Emergency Light with two round LED heads a test switch and recharge indicator. EMWL is UL 94V-0 flame rated, IP65, and Wet Location listed with an operating temperature range from 0°C to 40°C. EMWL is easy to install for wall and ceiling applications with its universal j-box mounting pattern and it provides a maximum 24-hour full recharge time.

- Residential
- Commercial
- Hospitality

**PHYSICAL**

Material	Injection-molded Thermoplastic ABS Housing
Mounting	Universal J-Box Mounting Pattern for Ceiling and Wall Mount Application
Lens	Polycarbonate
Finish	White, Black, Gray

**PERFORMANCE**

Warranty	5 years for fixture housing and electrical parts & 2 years for battery
Certifications	Wet Location, cULus, UL 94V-0 Flame Rating, CEC, FCC, DOE, RoHS Compliant
IP Rating	IP65
Operating Temperature	0°C to 40°C (32°F to 104°F)
Rated Life	L70 50,000 hours
CCT	6000K
CRI	80+
Beam Angle	120°

**ELECTRICAL**

Wattage	2.4W
Voltage	120/277V Dual Voltage
Power Factor	0.76
Dimmable	No
Battery	Built-in 3.6V 2000mAh Nickel cadmium battery for minimum 90 minutes emergency operation.

**ORDERING LOGIC**

EX: EMWL-WH

FAMILY	FINISH
<b>EMWL</b>	<input type="text"/>
	<b>WH</b> White
	<b>BK</b> Black
	<b>GR</b> Gray

