

PROJECT DATE

COMMENTS















## **ENERGY CHART**

SIZE	APERTURE DIAMETER inches	TOTAL DIAMETER inches	LUMENS	WATTAGE	EFFICACY Im/w
4	4.3	4.9	800	10	80

# **G4D** GIMBAL 4" DOWNLIGHT LED

The G4D Series is intended for new construction and retrofit applications. G4D is equipped with strong spring-loaded retention clips for recessing into ceilings up to 1" thick without the need for a J-Box or recessed housing. G4D is suitable for damp locations where architectural accents are desired.

- · Residential
- · Commercial
- Hospitality

#### **PHYSICAL**

Material	Aluminum
Mounting	Recessed
Lens	PMMA
Finish	White

#### **PERFORMANCE**

Warranty	5 years
Certifications	Damp Location, ETL, CE, Energy Star, FCC, ROHS Compliant
Rated Life	L70 50,000 hours
ССТ	Field Selectable 3CCT: 3000K/4000K/5000K
CRI	80+
Beam Angle	90° Tilt / 360° Rotation

## **ELECTRICAL**

Wattage	10W
Voltage	120V
Power Factor	>0.95
Dimmable	100% - 5% Triac Dimming

EX: G4D-FS3 **ORDERING LOGIC** 

FAMILY ССТ G4D FS3

**FS3** Field Selectable



## **DIMENSIONS**

