

PROJECT _____ DATE _____

COMMENTS _____



ENERGY CHART

SIZE	DIAMETER inches	LUMENS	WATTAGE	EFFICACY lm/w
4	4.3	810	9	90

G4P GIMBAL 4" PANEL LED

The G4P Series offers a low-profile, high output recessed mount LED luminaire that meets Energy Star's efficiency standards.

- Residential
- Commercial
- Hospitality

PHYSICAL

Material	Aluminum
Mounting	Recessed
Lens	PS Diffuser
Finish	White
CCT	Single CCT, Field Selectable 3CCT: 2700K, 3000K, 3500K, 4000K, 5000K
CRI	80+
Adjustability	25° Tilt

PERFORMANCE

Warranty	5 years
Certifications	Damp Location, IC Rated, ETL, CE, Energy Star, FCC, ROHS Compliant
IP Rating	IP44
Rated Life	50,000 hours
Operating Temperature	-10°C to 40°C (14°F to 104°F)

ELECTRICAL

Wattage	9W
Voltage	120V
Power Factor	>0.90
Dimmable	Triac Dimming

ORDERING LOGIC

EX: G4P-27

FAMILY	CCT	OPTIONS
G4P		
27	2700K	CC Custom Configurations FOR ADDITIONAL OPTIONS CONTACT SALES@SAGELIGHTING
30	3000K	
35	3500K	
40	4000K	
50	5000K	
FS3	Field Selectable 3000K / 4000K / 5000K	