



PROJECT

DATE

COMMENTS



















PHYSICAL

Material	Steel
Mounting	Surface
Lens	Polycarbonate Diffuser
Finish	Black, Brushed Nickel, White
Source	LED
ССТ	Single CCT, Field Selectable 3CCT, Field Selectable 5CCT: 2700K, 3000K, 3500K, 4000K, 5000K
CRI	80+ or 90+

PERFORMANCE

Warranty	5 years
Certifications	Damp Location, UL, CUL, CETL, ETL
IP Rating	IP44
Rated Life	50,000 hours
Operating Temperature	-20°C to 45°C (-4°F to 113°F)

ELECTRICAL

Wattage	15W
Voltage	120V
Power Factor	>0.95
Dimmable	Yes

ENERGY CHART

HEIGHT inches	WIDTH inches	LUMENS	WATTAGE	EFFICACY Im/w
9.0	9.0	1400	15	93.3

NOTES

ORDERING LOGIC EX: OMNI-27-80-BK

FAMILY		ССТ		CRI		FINISH		OPTIONS
ОМИІ								
	27	2700K	80	80+ CRI	ВК	Black	CC	Custom Configurations FOR ADDITIONAL OPTIONS CONTACT SALES@SAGE.LIGHTING
	30	3000K	90	90+ CRI	BN	Brushed Nickel		
	35	3500K			WH	White		
	40	4000K						
	50	5000K						
	FS3	Field Selectable 2700K/3000K/3500K						
	FS5	Field Selectable 2700K/3000K/3500K/4000K/5000K						