

PROJECT	DATE
COMMENTS	





PL PARKING LOT LED DUSK-TO-DAWN

The PL Series offers a DLC Certified, IP66 wet location rated LED luminiare with optional occupancy sensors for maximum energy savings.

- Multiple Finish Options
- Standard 1-10V Dimming
- Multiple Mounting Options

PHYSICAL

Material	Die-Cast Aluminum
Mounting	Slip Fitter, Arm/Wall Bracket, Trunnion, Yoke Bracket
Lens	Polycarbonate Diffuser
Finish	Bronze
ССТ	Field Selectable: 3000K, 4000K, 5000K
CRI	80+

PERFORMANCE

Warranty	5 years
Certifications	CETL, DLC
IP Rating	IP66
Rated Life	>100,000 Hours
Operating Temperature	-40°C to 50°C (-40°F to 122°F)

ENERGY CHART

DELIVERED LUMENS	WATTAGE	EFFICACY Im/w
18000	100	180
25500	150	170
32000	200	160

ELECTRICAL

Wattage	Field Selectable: 100W, 150W, 200W
Voltage	120-277VAC
Dimmable	1-10V
Surge Protector	Yes
Control	Dusk-to-Dawn Photocell

ORDERING LOGIC

FAMILY

ACCESSORIES ORDERING LOGIC (ORDER SEPARATELY)

EX: PL-SF

FAMILY	DISTRIBUTION		OPTIONS	
PL				
	3	Type 3	MS	Motion Sensor
	4	Type 4		
	5	Type 5		


PL				
	SF	Slip Filter	RPM6	Round Pole Mount, 6" Pole
	SPM	Square Pole Mount	тв	Trunnion Bracket
	RPM4	Round Pole Mount, 4" Pole	UB	"U" Bracket
	RPM5	Round Pole Mount, 5" Pole	RC	Remote Control for Motion Sensor

ACCESSORIES



PL PARKING LOT LED DUSK-TO-DAWN


DIMENSIONS



6.4"

DISTRIBUTION

6.8"





PL PARKING LOT LED DUSK-TO-DAWN

MOUNTING & SENSORS

200W ARM WITH SENSOR

200W SLIP FITTER ARM WITH SENSOR

200W TRUNION BRACKET WITH SENSOR

200W YOKE WITH SENSOR









ADDITIONAL IMAGERY

150W WITH PHOTOCELL & FIELD SELECTABLE WATTAGE DIP SWITCH



200W WITH PHOTOCELL & FIELD SELECTABLE WATTAGE DIP SWITCH DIP SWITCH

8

- (?)





200W WITH COVER ON PHOTOCELL



OPTIONS



REV 2022 0516 ONS AND DETAILS ARE SUBJECT TO CHANGE WITHOUT NOTIFICATION. CONTACT TERRAIN SITE LIGHTING FOR UP TO DATE DETAILS. TERRAIN SITE LIGHTING • TERRAIN.LIGHTING