



TERRAIN SITE LIGHTING

PROJECT DATE

COMMENTS



IN STOCK



ENERGY CHART

HEIGHT inches	WIDTH inches	DELIVERED LUMENS	WATTAGE	EFFICACY lm/w
20	14.2	5200	40	130
20	14.2	7800	60	130
20	14.2	13000	100	130
20	14.2	2600/3900/5200/7800	20/30/40/60	130
20	14.2	10400/13000/15600/19500	80/100/120/150	130

PTR-QS POST TOP ROUND LED QUICK SHIP

The PTR-QS Series offers an IP65 wet location rated outdoor LED luminaire with an optional daylight sensor.

- Parking Lots
- Underpasses
- Perimeter / Area Lighting

PHYSICAL

Material	Die-Cast Aluminum
Mounting	3.0" Tenon
Lens	Glass
Finish	Black

PERFORMANCE

Warranty	5 years
Certifications	cETLus, DLC, FCC
IP Rating	IP65
Rated Life	L80 50,000 hours
Operating Temperature	-20°C to 45°C (-4°F to 113°F)
CCT	5000K, Field Selectable: 3000K/4000K/5000K
CRI	70+
Beam Angle	120°

ELECTRICAL

Wattage	40W, 60W, 100W, Field Selectable: 20W/30W/40W/60W, Field Selectable: 80W/100W/120W/150W
Voltage	120-277V
Power Factor	>0.9

ORDERING LOGIC

EX: PTR-QS-40-50

FAMILY	WATTAGE	CCT
PTR-QS	40 40W	50 5000K
	60 60W	
	100 100W	
	FS1 Field Selectable 20W / 30W / 40W / 60W	FS Field Selectable 3000K / 4000K / 5000K
FS2 Field Selectable 80W / 100W / 120W / 150W		



DIMENSIONS

