

PROJECT DATE

COMMENTS



IN STOCK



ENERGY CHART

SIZE	DIAMETER inches	LUMENS	FIELD SELECTABLE WATTAGE	EFFICACY lm/w	FIELD SELECTABLE CCT
4	4.0	600	8	75	2700K 3000K 3500K 4000K 5000K
		750	10	75	
		900	12	75	
6	6.0	900	12	75	
		1125	15	75	
		1350	18	75	

RDR ROUND DOWNLIGHT RETROFIT LED

The RDR series is ideal for retrofit applications where an existing housing is already installed. This high output recessed mount LED luminaire meets Energy Star efficiency standards and it's available with field selectable CCT.

- Residential
- Commercial
- Hospitality

PHYSICAL

Mounting	Recessed
Finish	White
CCT	Field Selectable: 2700K, 3000K, 3500K, 4000K, 5000K
CRI	90+
Beam Angle	120°

PERFORMANCE

Warranty	5 years
Certifications	Damp Location, CETL, Energy Star
Rated Life	L70 50,000 hours
Operating Temperature	-20°C to 50°C (-4°F to 122°F)

ELECTRICAL

Wattage	Field Selectable: 8W, 10W, 12W / Field Selectable: 12W, 15W, 18W
Voltage	120V
Power Factor	>0.9
Dimmable	100% - 10% Triac Dimming

ORDERING LOGIC

EX: RDR-4-FS1-WH

FAMILY	SIZE	WATTAGE	OPTIONS
RDR	<input type="text"/>	<input type="text"/>	<input type="text"/>
	4 Fits 4"	FS1 Field Selectable 8W / 10W / 12W	CC Custom Configurations FOR ADDITIONAL OPTIONS CONTACT SALES@SAGELIGHTING
	6 Fits 5" / 6"	FS2 Field Selectable 12W / 15W / 18W	