

PROJECT DATE

COMMENTS



ENERGY CHART

FINISH	HEIGHT inches	WIDTH inches	DELIVERED LUMENS (4000K)	WATTAGE	EFFICACY lm/w
BZ	3.3	8.6	50	4.5	11.1
SN	3.3	8.6	100	4.5	22.2

SL8L STEP LIGHT 8" LOUVER LED

SL8L is a 120-277V 8" LED louvered step light ideal for new construction applications where low level glare free path lighting is desired. SL8L is supplied with an aluminum faceplate and field selectable CCT. The plastic junction box is the size of a standard brick (8.54"W x 3.23"H x 2.23"D) with conduit knockouts on both sides for easy installation. SL8L is IP65 rated, wet location listed and available in multiple finishes.

- Residential
- Commercial
- Hospitality

PHYSICAL

Material	Aluminum Faceplate, Plastic Junction Box
Mounting	Recessed Wall Mount
Lens	Louver
Finish	Oil-Rubbed Bronze, Satin Nickel

PERFORMANCE

Warranty	3 years
Certifications	cETLus, Wet Location
IP Rating	IP65
Rated Life	L70 50,000 Hours
CCT	Field Selectable: 2700K, 3000K, 4000K
CRI	90+
Beam Angle	30°

ELECTRICAL

Wattage	4.5W
Voltage	120-277V
Dimmable	Triac Dimmable 10% to 100% at 120V

ORDERING LOGIC

EX: SL8L-BZ

FAMILY	FINISH
SL8L	<input type="text"/>
	BZ Bronze
	SN Satin Nickel



DIMENSIONS

