

PROJECT


COMMENTS

(ŲĮ US



DATE





ORDERING LOGIC – UNIVERSAL FACE VERSION

| FAMILY | | FACE COUNT | LETTI | ER COLOR | | OPERATION |
|--------|---|---|-------|----------|----|------------------------------------|
| SME | | U | | | | |
| | U | Universal SINGLE CLEAR / DOUBLE MIRROR | G | Green | AC | AC Only |
| | | | R | Red | EM | Emergency (Nickel-Cadmium Battery) |

ORDERING LOGIC – SINGLE OR DOUBLE FACE VERSION

| FAMILY | PANEL FINISH | FACE COUNT | LETTER COLOR | OPERATION |
|--------|-----------------|-----------------|--------------|--|
| SME | | | | |
| | CL Clear | S Single | G Green | AC Only |
| | MR Mirror | D Double | R Red | EM Emergency (Nickel-Cadmium Battery) |
| | WH White | | | |

SME SURFACE MOUNT EXIT SIGN LED

The SME Series offers a single or double, red or green LED face options complete with a test switch and recharge indicator. The SME is easy to install and provides a maximum 24-hour full recharge time.

- Residential
- Commercial
- Hospitality

PHYSICAL

| Material | Aluminum Housing with High Grade Acrylic Panel |
|--------------|--|
| Mounting | Universal Mounting (Top, Back, End) |
| Panel Finish | Clear, Mirror or White |
| Face Count | Single or Double |
| Letter Color | Green or Red |

PERFORMANCE

| Warranty | 5 years |
|-----------------------|-----------------------------|
| Certifications | Damp Location, UL, cULus |
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |

ELECTRICAL

| Wattage | 2.5W (Green), 3W (Red) |
|---------|--|
| Voltage | 120V-277VAC |
| Battery | 4.8V Nickel Cadmium 90-Minutes Emergency Operation |

EX: SME-CL-S-G-AC

EX: SME-U-G-AC