

SPR SLIM PANEL ROUND LED

The SPR Series offers a low-profile, high output surface mount LED luminaire that meets Energy Star's efficiency standards.

- Residential
- Commercial
- Hospitality

PROJECT DATE

COMMENTS



PHYSICAL

Mounting	Surface
Finish	White
CCT	3000K, 4000K, 5000K, Field Selectable
CRI	80+
Beam Angle	120°

PERFORMANCE

Warranty	5 years
Certifications	ETL, Energy Star, FCC
IP Rating	IP20
Rated Life	L70 50,000 hours
Operating Temperature	-20°C to 40°C (-4°F to +104°F)

ELECTRICAL

Wattage	6W, 12W, 18W, 24W
Voltage	120V
Power Factor	>0.90
Dimmable	100% - 10% Triac Dimming

ENERGY CHART

SIZE	HEIGHT inches	WIDTH inches	LUMENS	WATTAGE	EFFICACY lm/w
5	0.6	5.0	450	6	75
7	0.6	7.0	900	12	75
9	0.6	9.0	1530	18	85
12	0.6	12.0	2160	24	90

ORDERING LOGIC

EX: SPR-5-30

FAMILY	SIZE	CCT
SPR	5 5"	30 3000K
	7 7"	40 4000K
	9 9"	50 5000K
	12 12"	FS Field Selectable 3000K / 4000K / 5000K

DIMENSIONS

