

SPR-MS CLOSET-RATED SLIM PANEL ROUND LED WITH MOTION SENSOR

The SPR-MS Series offers a low-profile, high output surface mount LED luminaire with an integral PIR motion sensor that meets Energy Star's efficiency standards.

- Residential
- Commercial
- Hospitality

PROJECT _____ DATE _____

COMMENTS _____



PHYSICAL

Mounting	Surface
Finish	White
CCT	3000K, 4000K, 5000K, Field Selectable
CRI	80+
Beam Angle	120°

PERFORMANCE

Warranty	5 years
Certifications	ETL, Energy Star, FCC
IP Rating	IP20
Rated Life	L70 50,000 hours
Operating Temperature	-20°C to 40°C (-4°F to +104°F)

ELECTRICAL

Wattage	18W
Voltage	120V
Power Factor	>0.90
Dimmable	100% - 10% Triac Dimming

ENERGY CHART

DIAMETER inches	OVERALL DEPTH inches	DELIVERED LUMENS	WATTAGE	EFFICACY lm/w
9	0.6	1530	18	85

ORDERING LOGIC

EX: SPR-MS-9-30

FAMILY	SIZE	CCT
SPR-MS	9	
	9 9"	30 3000K 40 4000K 50 5000K FS Field Selectable 3000K / 4000K / 5000K

DIMENSIONS

Size 9

