

PROJECT DATE

COMMENTS



SPR-UNV SLIM PANEL ROUND LED 120-277V

The SPR-UNV series is a universal voltage, round shaped, low-profile, high output surface mount LED luminaire. SPR-UNV utilizes an aluminum housing for excellent heat dissipation with a smooth uniform polycarbonate lens. Corrosion and heat resistant powder coat finishes available in White, Black, Satin Nickel and Bronze. Dimmable to 5% with compatible Triac and ELV dimmers. SPR-UNV is damp location listed with a 3-year warranty.

- Residential
- Commercial
- Hospitality

PHYSICAL

Material	Aluminum
Mounting	Surface
Lens	Polycarbonate
Finish	Black, White, Satin Nickel, Bronze
Source	LED

PERFORMANCE

Warranty	3 year
Certifications	Damp Location, cETLus
IP Rating	IP44
Rated Life	L70 36,000 hours
CCT	Field Selectable: 2700K/3000K/3500K/4000K/5000K
CRI	90+

ENERGY CHART

SIZE	HEIGHT inches	DIAMETER inches	DELIVERED LUMENS	WATTAGE	EFFICACY lm/w
5	0.5	5	600	10	60
7	0.5	7	900	15	60
10	0.5	9.9	1200	20	60
15	0.5	15	2200	36	60

ELECTRICAL

Wattage	10W, 15W, 20W, 36W
Voltage	Universal (120-277V)
Dimmable	5% - 100% with compatible Triac and ELV dimmers at 120V Note: Dimmable only at 120V

ORDERING LOGIC

EX: SPS-UNV-4-FS-WH

FAMILY	SIZE	CCT	VOLTAGE	FINISH
SPR-UNV		FS		
	5 5"	FS Field Selectable 2700K / 3000K / 3500K / 4000K / 5000K	(blank) Universal (120-277V)	WH White
	7 7"			BK Black
	10 9.9"			SN Satin Nickel
	15 15"			BZ Bronze



DIMENSIONS

SIZE 5: 5"

SIZE 7: 7"

SIZE 10: 9.9"

SIZE 15: 15"

