

PROJECT DATE

COMMENTS













#### **ENERGY CHART**

SIZE	<b>HEIGHT</b> inches	WIDTH inches	DELIVERED LUMENS	WATTAGE	EFFICACY Im/w	
4	0.5	4.5	600	10	60	
6	0.5	6.3	900	15	60	
9	0.5	9.0	1200	20	60	
15	0.5	15	2200	36	60	

# **SPS-UNV** SLIM PANEL SQUARE LED 120-277V

The SPS-UNV series is a universal voltage, square shaped, low-profile, high output surface mount LED luminaire. SPS-UNV utilizes an aluminum housing for excellent heat dissipation with a smooth uniform polycarbonate lens. Corrosion and heat resistant powder coat finishes available in White, Black, Satin Nickel, and Bronze. Dimmable to 5% with compatible Triac and ELV dimmers. SPS-UNV is damp location listed with a 3-year warranty.

- Residential
- · Commercial
- Hospitality

### PHYSICAL

Material	Aluminum
Mounting	Surface
Lens	Polycarbonate
Finish	Black, White, Satin Nickel, Bronze
Source	LED

#### **PERFORMANCE**

Warranty	3 year
Certifications	Damp Location, cETLus
IP Rating	IP44
Rated Life	L70 36,000 hours
ССТ	Field Selectable: 2700K/3000K/3500K/4000K/5000K
CRI	90+

## **ELECTRICAL**


Wattage	10W, 15W, 20W, 36W
Voltage	Universal (120-277V)
Dimmable	5% - 100% with compatible Triac and ELV dimmers at 120V Note: Dimmable only at 120V

ORDERING LOGIC EX: SPS-UNV-4-FS-WH

FAMILY		SIZE		ССТ		VOLTAGE		FINISH
SPS-UNV		FS						
	4	4.5" x 4.5" x 0.5"	FS	Field Selectable 2700K/3000K/3500K/4000K/5000K	(blank)	Universal (120-277V)	WH	White
	6	6.3" × 6.3" × 0.5"					вк	Black
	9	9" x 9" x 0.5"					SN	Satin Nickel
	15	15" × 15" × 0.5"					ΒZ	Bronze



## **DIMENSIONS**



SIZE 6: 6.3" SIZE 9: 9" SIZE 15: 15"

