

PROJECT

DATE

COMMENTS



**DISCONTINUED**



## ENERGY CHART

SIZE	LUMENS	WATTAGE	EFFICACY lm/w
1 x 4	3375 - 5000	27 / 40	125
2 x 2	4500 - 4500	27 / 36	125
2 x 4	5000 - 6250	40 / 50	125

## ORDERING LOGIC

EX: TAL-22

FAMILY	SIZE	OPTIONS
<b>TAL</b>		
	<b>14</b> 1X4	<b>EM</b> Emergency Backup: 90 minutes
	<b>22</b> 2X2	<b>OS</b> Occupancy Sensor
	<b>24</b> 2X4	

## TAL TROFFER ARCHITECTURAL LED

The TAL Troffer is dry/damp location approved architectural LED with a high-diffusion lens. This troffer can be fully recessed or chain mounted. TAL can be ordered with fixed CCT and wattage, or it can be ordered with field selectable CCT and field selectable wattage.

- Hospitality
- Commercial
- Indoor

## PHYSICAL

Material	Die formed of 0.6mm cold-rolled steel body
Mounting	Chain, Recessed or Surface Mounted
Lens	Polycarbonate Diffuser
Finish	White Matte Powder Coat

## PERFORMANCE

Warranty	5 years
Certifications	Damp Location, cULus, cETLus, ETL, CE, DLC, RoHS Compliant
Rated Life	L70 50,000 hours
CCT	Field Selectable: 3500K, 4000K, 5000K
CRI	80+

## ELECTRICAL

Wattage	27W, 36W, 40W, 50W
Voltage	120-277V
Dimming	0-10V
Power Factor	>0.9
Driver Efficiency	>87% / THD<20%

## ACCESSORIES ORDERING LOGIC (ORDER SEPARATELY)

EX: TAL-SMK22

FAMILY	ACCESSORIES
<b>TAL</b>	
	<b>SMK14</b> 1x4 Surface Mount Kit
	<b>SMK22</b> 2x2 Surface Mount Kit
	<b>SMK24</b> 2x4 Surface Mount Kit
	<b>CM</b> Chain Mount Kit 3.28 FEET LONG

