

PROJECT \_\_\_\_\_ DATE \_\_\_\_\_

COMMENTS \_\_\_\_\_



### ENERGY CHART

TYPE	DIMENSIONS feet	LUMENS	WATTAGE	EFFICACY lm/w
1	2 X 2	3375	27	125
		4500	36	125
		2970-3960	27/36	110
2	1 X 4	4500	36	125
		2970-3960	27/36	110
3	2 X 4	5000	40	125
		6250	50	125
		4400-5500	40/50	110

## TAL TROFFER ARCHITECTURAL LED

The TAL Troffer is dry/damp location approved architectural LED with a high-diffusion lens. This troffer can be fully recessed or chain mounted. TAL can be ordered with fixed CCT and wattage, or it can be ordered with field selectable CCT and field selectable wattage.

- Hospitality
- Commercial
- Indoor

### PHYSICAL

Material	Die formed of 0.6mm cold-rolled steel body
Mounting	Recessed or Chain Mounted
Lens	Polycarbonate Diffuser
Finish	White Matte Powder Coat
CCT	Single CCT: 3000K, 4000K, 5000K, Field Selectable
CRI	80+

### PERFORMANCE

Warranty	5 years
Certifications	Damp Location, CUL, CETL, ETL, CE, DLC, ROHS Compliant
Rated Life	L70 50,000 hours

### ELECTRICAL

Wattage	27W, 36W, 40W, 50W
Voltage	120-277V
Dimming	0-10V
Power Factor	>0.9
Driver Efficiency	>87% / THD<20%

### ORDERING LOGIC

EX: TAL-1-27-30-R

FAMILY	TYPE	WATTAGE	CCT	MOUNTING	OPTIONS
TAL	1 2X2	27 27W	30 3000K	R Recessed STANDARD	22SM 2X2 Surface Mount Kit RECESSED MOUNTING ONLY
		36 36W	40 4000K	CM Chain Mount 3.28 FEET LONG	24SM 2X4 Surface Mount Kit RECESSED MOUNTING ONLY
		FS1 Field Selectable 27W / 36W	50 5000K		EM Emergency Backup: 90 minutes
	2 1X4	36 36W	FS Field Selectable 3000K / 3500K / 4000K		OS Occupancy Sensor
		FS1 Field Selectable 27W / 36W			CC Custom Configurations FOR ADDITIONAL OPTIONS CONTACT SALES@SAGE.LIGHTING
	3 2X4	40 40W			
		50 50W			
		FS2 Field Selectable 40W / 50W			