

PROJECT _____ DATE _____

COMMENTS _____



TDB TROFFER DOUBLE BARREL LED

The TDB Troffer is dry/damp location approved architectural LED with a high-diffusion dual lens. This troffer can be fully recessed or chain mounted.

- Hospitality
- Commercial
- Indoor

PHYSICAL

Material	Die formed of 0.6mm cold-rolled steel body
Mounting	Recessed or Chain Mounted
Lens	Polycarbonate Diffuser
Finish	White Matte Powder Coat
CCT	3000K, 3500K, 4000K, 5000K
CRI	80+

PERFORMANCE

Warranty	5 years
Certifications	Damp Location, CUL, CE, ROHS Compliant
Rated Life	L70 50,000 hours

ELECTRICAL

Wattage	24W, 36W, 42W, 50W, 68W
Voltage	120-277V
Dimming	0-10V
Power Factor	>0.9

ENERGY CHART

TYPE	DIMENSIONS feet	LUMENS	WATTAGE	EFFICACY lm/w
1	2X2	2640	24	110
		3960	36	110
2	2X4	4620	42	110
		5500	50	110
		7480	68	110

ORDERING LOGIC

EX: TDB-1-24-30-R

FAMILY	TYPE	WATTAGE	CCT	MOUNTING	OPTIONS
TDB	1 2X2	24 24W	30 3000K	R Recessed STANDARD	22SM 2X2 Surface Mount Kit RECESSED MOUNTING ONLY
		36 36W	35 3500K	CM Chain Mount 3.28 FEET LONG	24SM 2X4 Surface Mount Kit RECESSED MOUNTING ONLY
	2 2X4	42 42W	40 4000K	EM Emergency Backup: 90 minutes	
		50 50W	50 5000K	OS Occupancy Sensor	
		68 68W	CC Custom Configurations FOR ADDITIONAL OPTIONS CONTACT SALES@SAGE.LIGHTING		