

PROJECT DATE

COMMENTS



DISCONTINUED



ENERGY CHART

DIMENSIONS feet	DELIVERED LUMENS	WATTAGE	EFFICACY lm/w
2 X 2	2640	24	110
	3960	36	110
2 X 4	4400	40	110
	5500	50	110

ORDERING LOGIC EX: TDP-22

FAMILY	SIZE	OPTIONS
TDP		
	22 2X2	EM Emergency Backup: 90 minutes
	24 2X4	OS Occupancy Sensor

TDP TROFFER DUAL PANEL LED

The TDP Troffer is dry/damp location approved architectural LED with a high-diffusion dual lens and field selectable wattage and color temperature. This troffer can be fully recessed, surface, or chain mounted.

- Hospitality
- Commercial
- Indoor

PHYSICAL

Material	Die formed of 0.6mm cold-rolled steel body
Mounting	Recessed or Chain Mounted
Lens	Polycarbonate Diffuser
Finish	White Matte Powder Coat

PERFORMANCE

Warranty	5 years
Certifications	Damp Location, CUL, ROHS Compliant
Rated Life	L70 50,000 hours
CCT	Field Selectable: 3500K/4000K/5000K
CRI	80+

ELECTRICAL

Wattage	Field Selectable: 24W/36W, 40W/50W
Voltage	120-277V
Dimming	0-10V
Power Factor	>0.9

ACCESSORIES ORDERING LOGIC (ORDER SEPARATELY) EX: TDP-SMK22

FAMILY	OPTIONS
TDP	
	SMK22 2X2 Surface Mount Kit
	SMK24 2X4 Surface Mount Kit
	CMK Chain Mount Kit <small>3.28 FEET LONG</small>

