

PROJECT DATE

COMMENTS



TFL TROFFER FLAT LENS LED

The TFL Troffer is dry/damp location approved architectural LED with a high-diffusion, flat prismatic lens. This troffer can be fully recessed or chain mounted.

- Hospitality
- Commercial
- Indoor

PHYSICAL

Material	Die formed of 0.6mm cold-rolled steel body
Mounting	Recessed or Chain Mounted
Lens	Acrylic Diffuser
Finish	White Matte Powder Coat
CCT	3000K, 4000K, 5000K
CRI	80+

PERFORMANCE

Warranty	5 years
Certifications	Damp Location, CUL, CE, ROHS Compliant
Rated Life	L70 50,000 hours

ELECTRICAL

Wattage	40W, 45W, 60W
Voltage	90-277V
Dimming	0-10V
Power Factor	>0.9

ENERGY CHART

TYPE	DIMENSIONS feet	LUMENS	WATTAGE	EFFICACY lm/w
1	2 X 2	4400	40	110
2	1 X 4	4400	40	110
3	2 X 4	4950	45	110
		6600	60	110

ORDERING LOGIC

EX: TFL-1-40-30-R

FAMILY	TYPE	WATTAGE	CCT	MOUNTING	OPTIONS
TFL	1 2X2	40 40W	30 3000K	R Recessed STANDARD	22SM 2X2 Surface Mount Kit RECESSED MOUNTING ONLY
	2 1X4		40 4000K	CM Chain Mount 3.28 FEET LONG	24SM 2X4 Surface Mount Kit RECESSED MOUNTING ONLY
	3 2X4	45 45W 60 60W	50 5000K		EM Emergency Backup: 90 minutes OS Occupancy Sensor CC Custom Configurations FOR ADDITIONAL OPTIONS CONTACT SALES@SAGE.LIGHTING