

PROJECT \_\_\_\_\_ DATE \_\_\_\_\_

COMMENTS \_\_\_\_\_



### ENERGY CHART

DIMENSIONS feet	DELIVERED LUMENS	WATTAGE	EFFICACY lm/w
2 X 2	3600	30	120
	4800	40	120
2 X 4	4200	35	120
	5400	45	120

### ORDERING LOGIC

EX: TVL-22

FAMILY	SIZE	OPTIONS
TVL		
	22 2X2	EM Emergency Backup: 90 minutes
	24 2X4	OS Occupancy Sensor

## TVL TROFFER VOLUMETRIC LED

The TVL Troffer is dry/damp location approved volumetric LED with a high-diffusion dual lens and field selectable wattage and color temperature. This troffer can be fully recessed, surface, or chain mounted.

- Hospitality
- Commercial
- Indoor

### PHYSICAL

Material	Die formed of 0.6mm cold-rolled steel body
Mounting	Recessed, Surface, or Chain Mounted
Lens	Polycarbonate Diffuser
Finish	White Matte Powder Coat

### PERFORMANCE

Warranty	5 years
Certifications	Damp Location, CUL, ROHS Compliant
Rated Life	L70 50,000 hours
CCT	Field Selectable: 3500K/4000K/5000K
CRI	80+

### ELECTRICAL

Wattage	Field Selectable: 30W/40W, 35W/45W
Voltage	120-277V
Dimming	0-10V
Power Factor	>0.9

### ACCESSORIES ORDERING LOGIC (ORDER SEPARATELY)

EX: TVL-SMK22

FAMILY	OPTIONS
TVL	
	SMK22 2X2 Surface Mount Kit
	SMK24 2X4 Surface Mount Kit
CMK	Chain Mount Kit 3.28 FEET LONG