

PROJECT _____ DATE _____

COMMENTS _____



TVP TROFFER VERTICAL PANEL LED

The TVP Troffer is dry/damp location approved architectural LED with a high-diffusion dual lens. This troffer can be fully recessed or chain mounted.

- Hospitality
- Commercial
- Indoor

PHYSICAL

Material	Die formed of 0.6mm cold-rolled steel body
Mounting	Recessed or Chain Mounted
Lens	Polycarbonate Diffuser
Finish	White Matte Powder Coat
CCT	4000K, 5000K
CRI	80+

PERFORMANCE

Warranty	5 years
Certifications	Damp Location, CUL, CE, ROHS Compliant
Rated Life	L70 50,000 hours

ELECTRICAL

Wattage	36W, 50W
Voltage	110-277V
Dimming	0-10V
Power Factor	>0.9

ENERGY CHART

TYPE	DIMENSIONS feet	LUMENS	WATTAGE	EFFICACY lm/w
1	2 X 2	3960	36	110
2	2 X 4	5500	50	110

ORDERING LOGIC

EX: TVP-1-40-R

FAMILY	TYPE	CCT	MOUNTING	OPTIONS
TVP				
	1 2X2	40 4000K	R Recessed STANDARD	22SM 2X2 Surface Mount Kit RECESSED MOUNTING ONLY
	2 2X4	50 5000K	CM Chain Mount 3.28 FEET LONG	24SM 2X4 Surface Mount Kit RECESSED MOUNTING ONLY
				EM Emergency Backup: 90 minutes
				OS Occupancy Sensor
				CC Custom Configurations FOR ADDITIONAL OPTIONS CONTACT SALES@SAGELIGHTING