

PROJECT DATE

COMMENTS



DISCONTINUED



ENERGY CHART

DIMENSIONS feet	LUMENS	WATTAGE	EFFICACY lm/w
2 X 2	3960	36	110
2 X 4	5500	50	110

ORDERING LOGIC EX: TVP-22-30

FAMILY	SIZE	CCT	OPTIONS
TVP	22	30	EM Emergency Backup: 90 minutes
	24	40	
		50	OS Occupancy Sensor

TVP TROFFER VERTICAL PANEL LED

The TVP Troffer is dry/damp location approved architectural LED with a high-diffusion dual lens. This troffer can be fully recessed, surface, or chain mounted.

- Hospitality
- Commercial
- Indoor

PHYSICAL

Material	Die formed of 0.6mm cold-rolled steel body
Mounting	Recessed, Surface, Chain Mounted
Lens	Polycarbonate Diffuser
Finish	White Matte Powder Coat

PERFORMANCE

Warranty	5 years
Certifications	Damp Location, CUL, ROHS Compliant
Rated Life	L70 50,000 hours
CCT	3000K, 4000K, 5000K
CRI	80+

ELECTRICAL

Wattage	36W, 50W
Voltage	120-277V
Dimming	0-10V
Power Factor	>0.9

ACCESSORIES ORDERING LOGIC (ORDER SEPARATELY) EX: TVP-SMK22

FAMILY	OPTIONS
TVP	SMK22 2X2 Surface Mount Kit
	SMK24 2X4 Surface Mount Kit
	CMK Chain Mount Kit <small>3.28 FEET LONG</small>

