

PROJECT _____ DATE _____

COMMENTS _____



UC UNDER CABINET

The UC Under Cabinet LED Series is suitable for under cabinet mounting in dry locations. Capable of being converted to a fixed hard wire unit.

- Kitchen
- Bar
- Shelving

PHYSICAL

Operating Temperature	-30°C ~ 40°C (-22°F to +104°F)
Material	Low Profile Polycarbonate Cover
Mounting	Surface
Lens	Opal Glass Diffuser
CCT	2700K, 3000K, 4000K, 6000K
CRI	80+ or 90+

PERFORMANCE

Warranty	5 years
Certifications	ETL, CE

ENERGY CHART

SIZE	HEIGHT inches	WIDTH inches	WATTAGE
3	1.4	4.1	3
12	1.4	4.1	6
18	1.4	4.1	9
24	1.4	4.1	12

ELECTRICAL

Wattage	3W, 6W, 9W, 12W
Voltage	120V

ORDERING LOGIC

EX: UC-9-3-27-80

FAMILY	SIZE	WATTAGE	CCT	CRI	OPTIONS
UC	9 9"	3 3W	27 2700K	80 80+	CC Custom Configurations FOR ADDITIONAL OPTIONS CONTACT SALES@SAGE.LIGHTING
	12 12"	6 6W	30 3000K	90 90+	
	18 18"	9 9W	40 4000K		
	24 24"	12 12W	60 6000K		