

PROJECT DATE

COMMENTS









ENERGY CHART

SIZE	LENGTH inches	HEIGHT inches	DEPTH inches	DELIVERED LUMENS	WATTAGE	EFFICACY Im/w
8	8	7	1.2	450	6	75
16	16	7	1.2	750	12	62.5
24	24	7	1.2	850	14	60.7
32	32	7	1.2	950	16	59.4

ORDERING LOGIC

EX: UCS-8-FS1

UCS UNDER CABINET SELECTABLE LED

The UCS Under Cabinet Selectable LED Series is suitable for under cabinet mounting in dry/damp locations. Capable of being converted to a fixed hard wire unit and offers field selectable color temperatures.

- · Kitchen
- Bar
- · Shelving

PHYSICAL

Material	Aluminum
Mounting	Surface
Lens	Polycarbonate Diffuser
Finish	White
Included Accessories	4ft Power Cord with Plug, 6" White Jumper Cord, End to End Connection Hardware, 3/8" Conduit Connection Clip, Installing Screw Covers

PERFORMANCE

Warranty	5 years
Certifications	cETLus
Operating Temperature	-20°C to 40°C (-4°F to 104°F)
ССТ	Field Selectable: 3000K/4000K/5000K
CRI	90+

ELECTRICAL

Wattage	6W, 12W, 14W, 16W
Voltage	120V
Dimmable	Triac

ACCESSORIES ORDERING LOGIC (ORDER SEPARATELY)

EX: UCS-5PC

FAMILY	ACCESSORIES	
ucs		
	5PC	5' White Power Cord with Plug
	6JC	6" White Jumper Cord
	12JC	12" White Jumper Cord
	24JC	24" White Jumper Cord
	36JC	36" White Jumper Cord
	72JC	72" White Jumper Cord