



TERRAIN SITE LIGHTING

PROJECT DATE

COMMENTS



IN STOCK



ENERGY CHART

HEIGHT inches	LENGTH inches	DEPTH inches	DELIVERED LUMENS	WATTAGE	EFFICACY lm/w
8.1	6.5	3.8	2750	25	110
			3960	36	110

WPA-G2 WALL PACK ADJUSTABLE LED GEN 2

The WPA-G2 Series Wall Pack offers an IP65 wet location rated outdoor LED luminaire with a dusk to dawn photocell sensor.

- Parking Lots
- Underpasses
- Perimeter / Area Lighting

PHYSICAL

Material	Die-Cast Aluminum
Mounting	Wall Mounted
Lens	Glass
Finish	Bronze
CCT	3000K, 4000K, 5000K
CRI	70+

PERFORMANCE

Warranty	5 years
Certifications	ETL, CE, DLC, RoHS Compliant
IP Rating	IP65
Rated Life	50,000+ hours
Operating Temperature	-40°C to 60°C (-40°F to 140°F)

ELECTRICAL

Wattage	25W, 36W
Voltage	100-277V
Power Factor	>0.95

ORDERING LOGIC

EX: WPA-G2-25-30-70

FAMILY	WATTAGE	CCT	CRI
WPA-G2			70
	25 25W	30 3000K	70 70+
	36 36W	40 4000K	
		50 5000K	



DIMENSIONS

