


PROJECT DATE

COMMENTS



DISCONTINUED



ENERGY CHART

| SIZE | HEIGHT inches | WIDTH inches | DEPTH inches | DELIVERED LUMENS | WATTAGE | EFFICACY lm/w |
|------|------------------|-----------------|-----------------|---------------------|---------|------------------|
| 14 | 11.8 | 9.4 | 14.2 | 4800 | 40 | 120 |

WPFC WALL PACK FULL CUTOFF LED

The WPFC Series Wall Pack offers an IP65 wet location rated outdoor LED luminaire with a dusk to dawn sensor.

- Parking Lots
- Underpasses
- Perimeter / Area Lighting

PHYSICAL

| | |
|----------|----------------------|
| Material | Die-Cast Aluminum |
| Mounting | Wall Mount |
| Lens | Polycarbonate Lens |
| Finish | Black, Bronze, White |
| CCT | 3000K, 4000K, 5000K |
| CRI | 70+ |

PERFORMANCE

| | |
|-----------------------|--------------------------------|
| Warranty | 5 years |
| Certifications | ETL, CETL, CE, ROHS Compliant |
| IP Rating | IP65 |
| Rated Life | L70 50,000 hours |
| Operating Temperature | -40°C to 50°C (-40°F to 122°F) |

ELECTRICAL

| | |
|--------------|----------|
| Wattage | 40W |
| Voltage | 100-277V |
| Power Factor | >0.95 |
| Dimmable | 0-10V |

ORDERING LOGIC

EX: WPFC-40-30-BK

| FAMILY | WATTAGE | CCT | FINISH | OPTIONS |
|--------|---------|----------|-----------|--------------------|
| WPFC | 40 40W | 30 3000K | BK Black | DS Daylight Sensor |
| | 50 50W | 40 4000K | BZ Bronze | |
| | | 50 5000K | WH White | |

