

PROJECT DATE

COMMENTS



WRP WRAPAROUND LED

The WRP Wraparound Linear LED is a damp location listed LED luminaire with a high diffusion lens. This light can be surface mounted or suspended from the ceiling.

- Hospitality
- Commercial
- Indoor

PHYSICAL

Material	0.6mm Cold-Rolled Steel Body
Mounting	Surface or Suspended
Lens	Polycarbonate Diffuser
Finish	White Polyester Polymer
CCT	3000K, 4000K, 5000K, Field Selectable
CRI	80+

PERFORMANCE

Warranty	5 years
Certifications	Damp Location, UL, CETL, ETL, CE
Rated Life	L70 50,000 hours
Operating Temperature	Ambient Temperature not exceeding 40°C (104°F)

ELECTRICAL

Wattage	25W, 40W
Voltage	120-277V
Dimmable	1-10V

ENERGY CHART

SIZE	LENGTH feet	LUMENS	WATTAGE	EFFICACY lm/w
2	2	2750	25	110
4	4	4400	40	110

ORDERING LOGIC

EX: WRP-2-25-30-SM

FAMILY	SIZE	WATTAGE	CCT	MOUNTING	OPTIONS
WRP	2 2'	25 25W	30 3000K	SM Surface STANDARD	EB Emergency Integral Battery
	4 4'	40 40W	40 4000K	SP Suspended	MS Motion Sensor
			50 5000K		CC Custom Configurations
			FS Field Selectable 3000K / 4000K / 5000K		FOR ADDITIONAL OPTIONS CONTACT SALES@SAGELIGHTING