

PROJECT

DATE

COMMENTS



#### ENERGY CHART

SIZE	APERTURE DIAMETER inches	TOTAL DIAMETER inches	LUMENS	WATTAGE	EFFICACY lm/w
4	4.3	4.9	800	10	80

#### ORDERING LOGIC

EX: G4D-30

FAMILY	CCT
<b>G4D</b>	
	<b>30</b> 3000K
	<b>40</b> 4000K
	<b>50</b> 5000K
	<b>FS3</b> Field Selectable 3000K / 4000K / 5000K

## G4D GIMBAL 4" DOWNLIGHT LED

The G4D Series is intended for new construction and retrofit applications. G4D is equipped with strong spring-loaded retention clips for recessing into ceilings up to 1" thick without the need for a J-Box or recessed housing. G4D is suitable for damp locations where architectural accents are desired.

- Residential
- Commercial
- Hospitality

#### PHYSICAL

Material	Aluminum
Mounting	Recessed
Lens	PMMA
Finish	White
CCT	Single CCT, Field Selectable 3CCT: 3000K, 4000K, 5000K
CRI	80+
Beam Angle	90° Tilt / 360° Rotation

#### PERFORMANCE

Warranty	5 years
Certifications	Damp Location, ETL, CE, Energy Star, FCC, ROHS Compliant
Rated Life	L70 50,000 hours

#### ELECTRICAL

Wattage	10W
Voltage	120V
Power Factor	>0.95
Dimmable	100% - 5% Triac Dimming

**DIMENSIONS**

