

PROJECT	DATE
COMMENTS	



ENERGY CHART

SIZE	LUMENS	WATTAGE	EFFICACY lm/w
1 x 4	3375 - 5000	27 / 40	125
2 x 2	4500 - 4500	27 / 36	125
2 x 4	5000 - 6250	40 / 50	125

ORDERING LOGIC

EX: TAL-22

FAMILY	SIZE	OPTIONS
TAL		
14	1X4	EM Emergency Backup: 90 minutes
22	2X2	OS Occupancy Sensor
24	2X4	

TAL TROFFER ARCHITECTURAL LED

The TAL Troffer is dry/damp location approved architectural LED with a high-diffusion lens. This troffer can be fully recessed or chain mounted. TAL can be ordered with fixed CCT and wattage, or it can be ordered with field selectable CCT and field selectable wattage.

- Hospitality
- Commercial
- Indoor

PHYSICAL

Material	Die formed of 0.6mm cold-rolled steel body
Mounting	Chain, Recessed or Surface Mounted
Lens	Polycarbonate Diffuser
Finish	White Matte Powder Coat

PERFORMANCE

Warranty	5 years
Certifications	Damp Location, cULus, cETLus, ETL, CE, DLC, RoHS Compliant
Rated Life	L70 50,000 hours
CCT	Field Selectable: 3500K, 4000K, 5000K
CRI	80+

ELECTRICAL

Wattage	27W, 36W, 40W, 50W
Voltage	120-277V
Dimming	0-10V
Power Factor	>0.9
Driver Efficiency	>87% / THD<20%

ACCESSORIES ORDERING LOGIC (ORDER SEPARATELY)

EX: TAL-SMK22

FAMILY	ACCESSORIES
TAL	
SMK14	1x4 Surface Mount Kit
SMK22	2x2 Surface Mount Kit
SMK24	2x4 Surface Mount Kit
CM	Chain Mount Kit 3.28 FEET LONG

