

PROJECT

DATE

COMMENTS



PHYSICAL

Material	Metal Back Plate
Mounting	Surface
Lens	Polystyrene
Finish	Brushed Aluminum
Source	LED

PERFORMANCE

Warranty	5 years
Certification	Damp Location, ETL, Energy Star
Rated Life	L70 50,000 hours
CCT	Single CCT, Field Selectable 3CCT or Field Selectable 5CCT: 2700K, 3000K, 3500K, 4000K, 5000K
CRI	80+ or 90+

ELECTRICAL

Wattage	15W, 20W, 25W
Voltage	120V
Power Factor	>0.90
Dimmable	Yes



ENERGY CHART

DIAMETER inches	DELIVERED LUMENS	WATTAGE	EFFICACY lm/w
12	1200	15	80
14	1600	20	80
16	2000	25	80

RECOMMENDED DIMMERS

LEVITON MODELS

- 6674
- IPL06
- TBL03

LUTRON MODELS

- CT-600P

• CTCL-153P

• 6333-P

• DVCL-153P
- DLC-03P

• AYCL-153P

• S-600P

• LGCL-153P
- MACL-153MR-WH

• TG-600RP

• SCL-153P

ORDERING LOGIC

EX: BELT-12-27-80

FAMILY	DIAMETER	CCT	CRI
BELT			
	12 12"	27 2700K	80 80+ STANDARD
	14 14"	30 3000K	90 90+
	16 16"	35 3500K	
		40 4000K	
		50 5000K	
		FS3 Field Selectable 3000K / 4000K / 5000K	
		FS5 Field Selectable 2700K / 3000K / 3500K / 4000K / 5000K	